



# □ PWR-24AC-1-3-ULW



1 Camera 24VAC 3Amp Power Supply



The PWR-24AC-1-3-ULW is a CCTV power center engineered to manage remote camera and accessory power requirements in a NEMA 4X weatherproof enclosure. The PWR-24AC-1-3-ULW distribution module is designed with 1 individually fused output for powering up to 1 CCTV camera or accessory. It will provide 24Volts AC via distribution to one fused output with a total of 3.0 Amps continuous supply current.

## **Key Features**

- · Convenient screw and terminal and fuse access
- AC power LED indicator
- Includes transformer and spare fuses
- Lightweight molded fiberglass NEMA 4X weatherproof enclosure
- . Uses easy to find automotive style fuses

# **Technical Specifications**

#### PWR-24AC-1-3-ULW

FEATURES	
Convenient screw and terminal and fuse access	
AC power LED indicator	
Includes transformer and spare fuses	
Lightweight molded fiberglass NEMA 4X weatherproof enclosure	
Uses easy to find automotive style fuses	

SPECIFICATIONS	
Input	115VAC 50/60 HZ; 0.9 Amps
Output	One 24VAC individually fused
3 Amps 100 VA supply current at 70°F	
Fuse	5 Amps
NEMA 4X weatherproof enclosure	
Unit maintains camera synchronization	
Transformer	110VAC/24VAC, 100VA
Enclosure Dimensions	203.2 x 152.4 x 114.3mm (8" x 6" x 4.5")
UL listed	

### **Dimensions**

Unit: mm (inch)

