


Class 2 Energy Limiting Box Mount **BF Series**



Features

- Used in chimes, door bells, security systems, decorative lighting, furnaces, humidifiers, appliances, vending machines, intercom system type applications.
- Rugged, low noise design, indoor use only.
- Stripped wire input (primary) leads, screw terminal output (secondary).
- Mounted on box plate for easy installation.
- Input leads are black 6" minimum, on 240V models 240V lead is red.
- All models are designed for 50/60 Hz. operation - limited by built in circuit breaker.
- c UL us listed #E184371 - Class 2 Not inherently limited
- CSA certified (209651)



| Part No. | A.C. Input (Primary) | A.C. Output Secondary (RMS) | | Power Rating | Overall Dimensions | | |
|-------------|-------------------------|--------------------------------|------|-----------------|--------------------|------|------|
| | V (RMS) | V | A | VA | A | B | C |
| BF2F | 120 | 16 | 4.68 | 75 | 3.00 | 2.50 | 3.75 |
| BF5F | 240 | 16 | 4.68 | 75 | 3.00 | 2.50 | 3.75 |
| BF2G | 120 | 24 | 3.13 | 75 | 3.00 | 2.50 | 3.75 |
| BF5G | 240 | 24 | 3.13 | 75 | 3.00 | 2.50 | 3.75 |



Data subject to change without notice